

Technical data sheet 15C2

Specification Swivel chair, seat and back upholstered

Dimensions in mm	Backrest:	H:	610-670
	Seat:	H:	410-540
		W:	500
		D:	440-500
	Total:		
	rotai.	H:	1220
		W (no ArmR):	500
		W (ArmR):	705
		D:	690
Packaging data	Weight:	kg	20
	Volume:	m³	0,2



Basic equipment		Benefit
Backrest	Complete upholstery (fully covered), backrest height adjustable by hand wheel 60 mm. Back upholstery: 25 mm. Fabric covered by string method, not glued, 3-position lock with release mechanism.	The back mainly has to be supported in the area of the 4th and 5th lumbar vertebra. Can be adjusted to short and tall users. EN 1335 only demands locking in the foremost seating position. The backrest cannot accidently spring forward even after locking.
Upholstery	Breath actively moulding foam, CFC-, CHC-free (segregated foam), Seat: 55mm, fabric cover fixed by string method (fabric is not glued)	Upholstery is not glued ensuring optimal air movement, breathable
Mechanism	Synchronous mechanism with angle of beam of max.125°.	Synchronous mechanism of Interstuhl are designed in a way that they help to support optimally the body in every seating position and at the same time they relieve the change between the different seating positions.
Seat height adjustment	Infinitely seat height adjustment from 410 - 540 mm. Safety gas spring, self-supporting.	Even for people beyond the DIN range (i.e. taller than 184 cm and smaller than 151 cm) is offered the correct ergonomic posture.
Weight adjustment	Infinitely adjustable to the body weight from 45 - 120 kg.	Individual adjustment of the backrest and the back pressure to height and weight of the user.
Castors	Hard castors Ø 65 mm, load-dependent braked for soft floors (acc. to DIN EN 12529).	The chair doesn't roll away in an off-loaded condition, minimum risk of accident
Base	Polyamide base black. Textured surface.	Very high stability, longevity
Materials	All materials are segregated and recyclable. Dye penetration of plastic thus "colourfast" even with deep scratches.	Environmentally friendly
Standards	EN 1335 for office swivel chairs, GS symbol for tested safety, tested for contaminants, Ergonomics approved, Bifma tested.	High safety standard.
Certification	Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability. Quality Office, Blue Angel.	High quality product
Warranty and return	10 years warranty. Complete return and recycling guarantee.	High security and longevity by cost reduction. Exchange of spare parts within the guaranteed period free of charge.

Technical data sheet 15C2

Specification Swivel chair, seat and back upholstered

Dimensions in mm	Backrest:	H:	610-670
	Seat:	H:	410-540
		W:	500
		D:	440-500
	Total:		
		H:	1220
		W (no ArmR):	500
		W (ArmR):	705
		D:	690
Packaging data	Weight:	kg	20
	Volume:	m³	0,2



	Benefit
Soft castors Ø 65 mm, load-dependent braked for hard floors or felt glides (acc. DIN EN 12529).	The chair doesn't roll away in an off-loaded condition, minimum risk of accident
Aluminium base black, brilliant silver or polished.	Very high stability, longevity
Adjustable seat (8 steps, 50 mm).	The seat area can be extended for large users
Adjustable up to -5°.	By the inclination the pelvis is in an more upright position, the spinal column is straightened up, humpback is being avoided.
Adjustable lumbar support.	Through a mechanical rotation the lumbar support which is integrated in the back upholstery will be adjusted horizontally and will be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible.
Height adjustable (100 mm), infinitely width adjustable (2 x 25 mm), depth adjustable (50 mm), rotatable by (2 x 15°), soft surface.	Due to the adjustability the armrests relieve the neck and shoulder muscles.
Height adjustable (100 mm) and infinitely width adjustable (2 x 25 mm), soft surface.	Due to the adjustability the armrests relieve the neck and shoulder muscles.
For special qualities of cover different colours are possible on the seat an back upholstery.	Optical design.
Several fabrics in various qualities as well as leather available.	A great variety of design finishes
	for hard floors or felt glides (acc. DIN EN 12529). Aluminium base black, brilliant silver or polished. Adjustable seat (8 steps, 50 mm). Adjustable up to -5°. Adjustable lumbar support. Height adjustable (100 mm), infinitely width adjustable (2 x 25 mm), depth adjustable (50 mm), rotatable by (2 x 15°), soft surface. Height adjustable (100 mm) and infinitely width adjustable (2 x 25 mm), soft surface. For special qualities of cover different colours are possible on the seat an back upholstery. Several fabrics in various qualities as well as