

Technical data sheet 16M0

Specification Conference chair

| | | | |
|------------------|-----------|--------------|---------|
| Dimensions in mm | Backrest: | H: | 460 |
| | | | |
| | Seat: | H: | 420-540 |
| | | W: | 480 |
| | | D: | 475 |
| | Total: | H: | 1020 |
| | | W (no ArmR): | 480 |
| | | W (ArmR): | 665 |
| D: | | 490 | |
| Packaging data | Weight: | kg | 10,5 |
| | Volume: | m³ | 0,6 |



Basic equipment

Benefit

| | | |
|------------------------|---|---|
| Seat shell | Colour maintained throughout plastic parts, black. | Thus "colourfast" with deep scratches and abrasions. |
| Upholstery | Seat upholstery: 45 mm foam, back upholstery: 30 mm foam. Upholstery is unglued, ensuring optimal air movement, breathable. | Good seating comfort. |
| Seat height adjustment | Seat height adjustment infinitely variable from 420 - 540 mm. Self supporting safety gas spring. | Even those outside the DIN range (i.e. taller than 192 cm and smaller than 151 cm) are offered the correct ergonomic posture. |
| Castors Ø 65 mm | Hard double castors, load dependent braked, for soft floors. (Acc. to DIN EN 12529). | The chair does not roll away in an off loaded position, minimum risk of accident. |
| Base | Colour maintained throughout plastic base, as colour finish (plastic parts). | Thus "colourfast" with deep scratches and abrasions. |
| Materials | All materials are segregated and recyclable. | Environmentally friendly. |
| Standards | EN 16139 for visitor chairs. GS-Symbol for tested safety and tested for contaminants. | High safety and comfort. |
| Certification | Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability. Quality Office, Blue Angel, Bifma e3 level Platin. | High quality product. |
| Warranty and return | 10 years warranty. Complete return and recycling guarantee. | Exchange of parts free of charge, within the guaranteed period. |

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet 16M0

Specification Conference chair

| | | | |
|------------------|-----------|--------------|---------|
| Dimensions in mm | Backrest: | H: | 460 |
| | | | |
| | Seat: | H: | 420-540 |
| | | W: | 480 |
| | | D: | 475 |
| | Total: | H: | 1020 |
| | | W (no ArmR): | 480 |
| | | W (ArmR): | 665 |
| D: | | 490 | |
| Packaging data | Weight: | kg | 10,5 |
| | Volume: | m³ | 0,6 |



| Options | | Benefit |
|--|---|--|
| Colour finish | Seat shell and base in polyamide, colour maintained throughout, as plastic parts, white. | Thus "colourfast" with deep scratches and abrasions. Visual appeal. |
| Castors/Glides | Soft double castors, black, load dependent braked, for hard floors or glides. (Acc. to DIN EN 12529). | The chair does not roll away in an off loaded position, minimum risk of accident. |
| Base | Aluminium powder coated brilliant silver or polished. | Very high stability, Very high stability, longevity. |
| Material (fabric) | Several fabric collections and leather in various colours. | During the design of the chair several colours and upholstery materials are available. |
| Two colour design | For special qualities of cover different colours are possible on the seat and back upholstery. | Optical design. |
| Disassembly instructions are available upon request for any interstuhl product | | |