

Technical data sheet 5V60

Specification Cantilever frame low, design 2

| | | | | |
|------------------|-----------|-----------|------|-----|
| Dimensions in mm | Backrest: | H: | 440 | |
| | | Seat: | H: | 445 |
| | | | W: | 515 |
| | | | D: | 448 |
| | Total: | H: | 895 | |
| | | W (ArmR): | 600 | |
| D: | | 630 | | |
| Packaging data | Weight: | kg | 14,0 | |
| | Volume: | m³ | 0,51 | |



Basic equipment

Benefit

| | | |
|----------------------|--|--|
| Backrest/ Seat shell | Low. Plastic shell visible from the back, black coloured throughout. Colourfast and resistant to deep scratches and abrasions. | Great seating comfort due to the ergonomically designed backrest. High durability. Antishock protection. |
| Upholstery | Quilted back of backrest. Seat, back upholstered, with independently upholstered side panels. Mould foam, CFC and CHC free (segregated). Seat: 45mm foam + 10mm quilted cotton wool, back: 40mm foam + 10mm quilted cotton wool. Upholstery without adhesives. | Good seating comfort and great posture support. Ideal microclimate due to non-glued upholstery. |
| Frame | Cantilever, tubular steel Ø 22 mm, powder coated, black. | High level of stability, longevity as well as great support due to the bounce of the cantilever. |
| Armrests | Black plastic. | Neck muscles are relieved due to armrests. |
| Materials | All materials are segregated and recyclable. | Environmentally friendly, help to protect resources. |
| Norms | DIN EN 16139 seating furniture for project areas, GS-symbol for being tested on safety, Tested for Contaminants. | High level of safety and comfort. |
| Certifications | Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability. Blue Angel, Bifma e3 level Platin. | High-quality product. |
| Warranty and Return | 10 years warranty. Complete return and recycling guarantee. | Exchange of parts, free of charge within the guaranteed period. |

Technical data sheet 5V60

Specification Cantilever frame low, design 2

| | | | |
|------------------|-----------|-------|--------|
| Dimensions in mm | Backrest: | H: | 440 |
| | | Seat: | H: 445 |
| | | W: | 515 |
| | | D: | 448 |
| Total: | H: | 895 | |
| | W (ArmR): | 600 | |
| | D: | 630 | |
| Packaging data | Weight: | kg | 14,0 |
| | Volume: | m³ | 0,51 |



| Options | Benefit | |
|----------------------|---|--|
| Backrest/ Seat shell | White coloured throughout. Colourfast and resistant to deep scratches and abrasions. | High durability level. |
| Frame | Cantilever, tubular steel Ø 22 mm, powder coated, white or chrome. | High level of stability, longevity, great design. |
| Armrests | With leather cover. | Neck muscles are relieved due to armrests. Great comfort for upper arms due to the soft surface. |
| Glides | Felt glides for hard floors. | Chair stability, gentle to the flooring. |
| Materials | Various fabric and leather ranges are available (please refer to price list and fabric card samples). | Various design possibilities. |