interstuhl

Technical data sheet 100S

Specification Conference stool

Dimensions in mm

| | Seat: | H: W: D: | 410-510 480 480 |
|----------------|--------------------|--------------------|-----------------------|
| | Total: | H: W (no ArmR): | 600 580 |
| Packaging data | Weight: Volume: | D: kg m³ | 590 19 0,31 |



| Basic equipment | | Benefit |
|----------------------------|---|---|
| Upholstery | Breath actively moulding foam, CFC - CHC- free (segregated foam). Seat: 60 mm, foam + 10 mm decron layer. | Paddings are unglued, ensuring optimal air movement. Breathable. |
| Sprung column | Sprung column also in lowest position. | Sprung column enables attenuation of the sitting impulse, what saves the spinal column. |
| Conference glides | Hard conference glides for soft floors. | Optimal standing position of the chair. Protection of the floor. |
| Base | Aluminium base four legs with conference glides. | High stability, longevity. |
| Metal parts, colour finish | Powder coated white. | With a design very interesting for the eyes. |
| Materials | All materials are segregated and recyclable. | Environmentally friendly. |
| Standards | GS-symbol for tested safety and toxic agents. | High security and comfort. |
| Certification | Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Health and Safety Management System DIN EN ISO 45001:2018, EcoVadis Gold. Commitment to sustainability. | High-quality product. |
| Warranty and return | 10 years full warranty. Complete return and recycling guarantee. | Exchange of parts free of charge within the guaranteed period. |

Disassembly instructions are available upon request for any interstuhl product

interstuhl

Technical data sheet 100S

Specification Conference stool

Dimensions in mm

| | Seat: Total: | H: W: D: H: W (no ArmR): | 410-510 480 480 600 580 |
|----------------|--------------------|--------------------------------------|-------------------------------------|
| | | D: | 590 |
| Packaging data | Weight: Volume: | kg m³ | 19 0,31 |



| Options | | Benefit |
|----------------------------|---|---|
| Castors/Glides | Soft conference glides. Hard double castors, load-dependent braked, for soft floors or soft double castors, load dependent braked for hard floors. (Acc. to DIN EN 12529). | With castors, the chair does not roll away in an off-loaded condition, minimum risk of accident. With glides, optimal position of the chair, protection of the floor. |
| Metal parts, colour finish | Metal parts brushed silver, polished. | With a design very interesting for the eyes. |
| Base | 5-arm aluminium base with castors. | Very high stability, longevity. |
| Covers | Several fabric qualities and leather. | There are various colours and cover materials to choose from for designing the chair. |

Disassembly instructions are available upon request for any interstuhl product