

Technical data sheet 450B

Specification Four legs with armrests

Dimensions in mm

Seat:	H:	470
	W:	450
	D:	410
Total:	H:	930
	W (ArmR):	595
	D:	595

Packaging data	Weight:	kg	7,5
	Volume:	m³	0,4



Basic equipment

Benefit

Backrest	Upholstered mesh backrest (10 mm Schaum). Carrier material, backrest (from the back) always black.	
Upholstery	Seat upholstery: 55 mm foam.	Great seating comfort.
Frame	Tubular steel frame Ø 22 x 2,5 mm, powder coated as colour finish (plastic parts).	
Seat carrier.	Plastic.	
Stackability.	6 chairs.	Diverse use of space.
Plastic parts	Colour maintained throughout, black.	Colourfast and resistant to deep scratches and abrasions.
Glides	Plastic glides for soft floors.	Ideal stability.
Armrests	Plastic, colour maintained throughout, black.	The armrests relieve the neck and shoulder muscles.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Standards	EN 16139 for visitor chairs. GS-Symbol for tested safety and tested for contaminants.	High quality and great comfort.
Certification	Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability. Blue Angel, Bifma e3 level Platin.	High-quality product.
Warranty and return	10 years warranty. Complete return and recycling guarantee.	Exchange of parts free of charge within the guaranteed periods.

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet 450B

Specification Four legs with armrests

Dimensions in mm

Seat:	H:	470
	W:	450
	D:	410
Total:	H:	930
	W (ArmR):	595
	D:	595

Packaging data	Weight:	kg	7,5
	Volume:	m³	0,4



Options		Benefit
Plastic parts and frame	White.	Optical design.
Frame	Powder coated brilliant-silver or chromed.	Optical design.
Glides	Felt glides for hard floors.	Ideal stability and protection of the floor.
Materials (fabric)	Several fabric collections in various colours.	Individual design.

Disassembly instructions are available upon request for any interstuhl product