

Technical data sheet SU111

Specification Visitor chair, Four legs, not upholstered

Dimensions in mm	Backrest:	H:	400
		Seat:	H: 430
	Total:	W:	460
		D:	450
		H:	825
		W (no ArmR):	540
Packaging data	Weight:	kg	5.5
		Volume:	m³ 0,3
	W (ArmR):	580	
		D:	515



Basic equipment

Benefit

Seat and Backrest	Seat and back: polypropylene shell with Flex-Function. Ergonomically shaped; Rear side high gloss polished.	High quality appearance and ergonomic sitting.
Colour Design	Polypropylene shell available in the following colours: white (3283), black (3217), petrol (3A01), grey-blue (3A02), nude (3A03), or mustard (3A04).	Various design possibilities.
Frame	Four legged: Steel tube, powder-coated, white or black. Round tube Ø: 18 mm. Wall thickness: 2 mm.	Very good stability, longevity. The coating ensures an attractive surface even with intensive use.
Stackability	Stacking height: 5 pieces. Stacking protection included. If loop armrests are selected, the model will no longer be stackable.	Space-saving stowage possibility.
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are pure and recyclable.	Environmentally friendly.
Standards	GS-symbol for tested safety, tested for contaminants.	High level of safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Health and Safety Management System DIN EN ISO 45001:2018, EcoVadis Gold. Commitment to sustainability.	High-quality product.
Warranty and return	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet SU111

Specification Visitor chair, Four legs, not upholstered

Dimensions in mm	Backrest:	H:	400	
		Seat:	H:	430
			W:	460
			D:	450
	Total:	H:	825	
		W (no ArmR):	540	
		W (ArmR):	580	
D:		515		
Packaging data	Weight:	kg	5.5	
	Volume:	m ³	0,3	



Options	Benefit
<p>Frame</p> <p>Four legged: Steel tube, chromed. Round tube Ø: 18 mm. Wall thickness: 2 mm.</p>	<p>Very good stability, longevity. High quality appearance.</p>
<p>Glides</p> <p>Felt glides for hard floors, black.</p>	<p>Optimum stability of the chair. Spares the floor.</p>
<p>Armrests</p> <p>Open armrest or loop armrest (round tube Ø16 mm) in frame colour with black rubber pad.</p>	<p>The armrests relieve the neck and shoulder muscles.</p>
<p>Row connector</p> <p>Extendable row connector, chrome-plated.</p>	<p>Ability to connect chairs to rows of chairs.</p>

Disassembly instructions are available upon request for any interstuhl product