

Technical data sheet SU123

Specification Visitor chair, cantilever frame, seat&back uphol.

Dimensions in mm	Backrest:	H:	400	
		Seat:	H:	450
			W:	460
			D:	450
	Total:	H:	835	
		W (no ArmR):	500	
W (ArmR):		580		
D:		545		
Packaging data	Weight:	kg	8,5	
	Volume:	m³	0,3	



Basic equipment

Benefit

Seat and Backrest	Seat and back: polypropylene shell with Flex-Function. Ergonomically shaped; Rear side high gloss polish.	High quality appearance and ergonomic sitting.
Colour Design	Polypropylene shell available in the following colours: white (3283), black (3217), petrol (3A01), grey-blue (3A02), nude (3A03), or mustard (3A04).	Various design possibilities.
Upholstery	Seat and back upholstered. Foam thickness 10 mm.	Good seating comfort.
Frame	Cantilever frame: Steel tube, powder-coated, white or black. Round tube Ø: 22 mm. Wall thickness: 2,5 mm.	Very good stability, longevity. The coating ensures an attractive surface even with intensive use.
Stackability	Stacking height: 5 pieces. Stacking protection included. If loop armrests are selected, the model will no longer be stackable.	Space-saving stowage possibility.
Materials	All materials are pure and recyclable.	Environmentally friendly.
Standards	Tested for contaminants.	High level of safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Health and Safety Management System DIN EN ISO 45001:2018, EcoVadis Gold. Commitment to sustainability.	High-quality product.
Warranty and return	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet SU123

Specification Visitor chair, cantilever frame, seat&back uphol.

Dimensions in mm	Backrest:	H:	400	
		Seat:	H:	450
			W:	460
			D:	450
	Total:	H:	835	
		W (no ArmR):	500	
		W (ArmR):	580	
D:		545		
Packaging data	Weight:	kg	8,5	
	Volume:	m³	0,3	



Options		Benefit
Materials (fabric)	Various fabrics in a variety of colours are available.	Individual design.
Frame	Cantilever frame: Steel tube, chromed. Round tube Ø: 22 mm. Wall thickness: 2,5 mm.	Very good stability, longevity. High quality appearance.
Glides	Felt glides for hard floors, transparent.	Optimum stability of the chair. Spares the floor.
Armrests	Open armrest or loop armrest (round tube Ø16 mm) in frame colour with black rubber pad.	The armrests relieve the neck and shoulder muscles.

Disassembly instructions are available upon request for any interstuhl product