

Technical data sheet SU164

Specification Visitor chair, Four legs wood, fully upholstered

Dimensions in mm	Backrest:	H:	400
		Seat:	H: 440
	Total:	W:	460
		D:	450
		H:	825
		W (no ArmR):	460
Packaging data	Weight:	kg	8,2
		Volume:	m³ 0,3
		W (ArmR):	580
		D:	515



Basic equipment

Benefit

Seat and Backrest	Seat and back: polypropylene shell with Flex-Function. Ergonomically shaped; fully upholstered.	High quality appearance and ergonomic sitting.
Upholstery	Foam thickness: 10 mm, pad thickness approx. 15 mm.	Good seating comfort.
Frame	Four legs, Oak.	Very good stability and high quality look.
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are pure and recyclable.	Environmentally friendly.
Standards	GS-symbol for tested safety, tested for contaminants.	High level of safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Health and Safety Management System DIN EN ISO 45001:2018, EcoVadis Gold. Commitment to sustainability.	High-quality product.
Warranty and return	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet SU164

Specification Visitor chair, Four legs wood, fully upholstered

Dimensions in mm	Backrest:	H:	400	
		Seat:	H:	440
			W:	460
			D:	450
	Total:	H:	825	
		W (no ArmR):	460	
		W (ArmR):	580	
D:		515		
Packaging data	Weight:	kg	8,2	
	Volume:	m³	0,3	



Options	Benefit	
Materials (fabric)	Various fabrics in a variety of colours are available.	Individual design.
Glides	Felt glides for hard floors, black.	Optimum stability of the chair. Spares the floor.
Armrests	Open armrest or loop armrest (round tube Ø16 mm) in frame colour with black rubber pad.	The armrests relieve the neck and shoulder muscles.

Disassembly instructions are available upon request for any interstuhl product